



GOL Pump Technology INC



GOL Pump Technology INC

Supply , Import , Export Water Pumps

E-mail : info@golpumps.com

www.golpumps.com

Tel : +1(786) 615-8984 & (786) 452-9775

Fax: +1(786) 615-7043

6520 NW 77th Ct Zip: 33166

Miami (FL) United States





WATER PUMPS

GASOLINE WATER PUMPS



GASOLINE TRASH PUMPS



GASOLINE HIGH LIFT PUMPS



GASOLINE CHEMICAL PUMPS



GASOLINE WATER PUMPS													
GASOLINE TRASH PUMPS													
GASOLINE HIGH LIFT PUMPS													
GASOLINE CHEMICAL PUMPS													



GASOLINE WATER PUMPS



XG10

- 1.Perfect for homeowners, gardeners, boat owners, and more.
- 2.The XG10 is lightweight, compact, and easy to use.
- 3.The XG10 is easy to carry wherever you need it.
- 4.Uses regular gasoline - no mixing of oil and gas!
- 5.At only 7kg, the WX10 is easily portable.

Model	XG10
Pump	
Pump type	Centrifugal Pump
Flow(m ³ /H)	8
Suction Port Diameter(mm/inch)	25/1
Discharge Port Diameter(mm/inch)	25/1
Total Head Lift(m)	29
Suction Head Lift(m)	7
Engine	
Model	S35
Engine Type	4-stroke Gasoline Engine
Displacement (cc)	31
Max Power Output(W)	800
Starting System	Recoil
Engine Oil Capacity (ml)	70
Recommended Oil	SAE 10W-30
Fuel Tank Size (L)	0.5
Packing Details	
Outside Packing Dimensions (mm) (L x W x H)	345×265×315
Net Wiegth (kg)	6.5
Certification	CE/EC/EPA/CARB



WG20/30

- 1.The engine is easy starting and provides ample power for the toughest conditions.
- 2.The WG Serial features Graphite ceramics seals for extended wear.
- 3.The frame protects the pump, while offering a convenient tie down location for transport.
- 4.The cast iron volute and impeller reduces case wear, increasing the life of the pump.
- 5.Protects the pump by shutting the engine off when low oil is detected.

Model	WG20	WG30
Pump		
Pump type	Centrifugal Pump	
Flow(m ³ /H)	35	55
Suction Port Diameter(mm/inch)	50/2	80/3
Discharge Port Diameter(mm/inch)	50/2	80/3
Total Head Lift(m)	30	30
Suction Head Lift(m)	7	7
Engine		
Model	GB200	GB200
Engine Type	4-stroke Gasoline Engine	
Displacement (cc)	196	196
Max Power Output(W)	4500	4500
Starting System	Recoil	Recoil
Engine Oil Capacity (ml)	600	600
Recommended Oil	SAE 10W-30	SAE 10W-30
Fuel Tank Size (L)	2.6	2.6
Packing Details		
Outside Packing Dimensions (mm) (L x W x H)	515×415×415	530×415×445
Net Wieght (kg)	24	26
Certification	CE/EC/EPA	CE/EC/EPA

WG60

- 1.The engine is easy starting and provides ample power for the toughest conditions.
- 2.The WG60 features Graphite ceramics seals for extended wear.
- 3.The frame protects the pump, while offering a convenient tie down location for transport.
- 4.The rigid-mount cast iron volute reduces case wear, increasing the life of the pump.
- 5.Protects the pump by shutting the engine off when low oil is detected.
- 6.Fit for using on mass flow irrigation and drainage.

Model	WG60
Pump	
Pump type	Centrifugal Pump
Flow(m ³ /H)	150
Suction Port Diameter(mm/inch)	150/6
Discharge Port Diameter(mm/inch)	150/6
Total Head Lift(m)	20
Suction Head Lift(m)	5
Engine	
Model	190F
Engine Type	4-stroke Gasoline Engine
Displacement (cc)	420
Max Power Output(W)	8400
Starting System	Recoil
Engine Oil Capacity (ml)	1100
Recommended Oil	SAE 10W-30
Fuel Tank Size (L)	5.2
Packing Details	
Outside Packing Dimensions (mm) (L x W x H)	750×550×685
Net Wieght (kg)	75
Certification	EC



GASOLINE TRASH PUMPS



TG20/30

- 1.The engine is easy starting and provides ample power for the toughest conditions.
- 2.The TG features abrasion-resistant silicone-carbide seals for extended wear.
- 3.The frame protects the pump, while offering a convenient tie down location for transport.
- 4.The cast iron volute and impeller reduces case wear, increasing the life of the pump.
- 5.Protects the pump by shutting the engine off when low oil is detected.
- 6.The TG is designed for quick and easy service.
- 7.Providing metal filter with solid size capacity 14mm.

Model	TG20	TG30
	Pump	
Pump type	Centrifugal Pump	
Flow(m ³ /H)	35	55
Suction Port Diameter(mm/inch)	50/2	80/3
Discharge Port Diameter(mm/inch)	50/2	80/3
Total Head Lift(m)	30	25
Suction Head Lift(m)	6	6
Allowed Max. Solid Size Diameter(mm)	14	22
	Engine	
Model	GB200	GB200
Engine Type	4-stroke Gasoline Engine	4-stroke Gasoline Engine
Displacement (cc)	196	196
Max Power Output(W)	4500	4500
Starting System	Recoil	Recoil
Engine Oil Capacity (ml)	600	600
Recommended Oil	SAE 10W-30	SAE 10W-30
Fuel Tank Size (L)	2.6	2.6
	Packing Details	
Outside Packing Dimensions (mm) (L x W x H)	570×495×485	570×495×485
Net Wieght (kg)	33	38
Certification	CE/EC/EPA	CE/EC/EPA





GASOLINE HIGH LIFT PUMPS



HG15/20/30

- 1.The engine is easy starting and provides ample power for the toughest conditions.
- 2.The HG features Graphite ceramics seals for extended wear.
- 3.The frame protects the pump, while offering a convenient tie down location for transport.
- 4.Protects the pump by shutting the engine off when low oil is detected.

Model	HG15	HG20	HG30
	Pump		
Pump type	Double Centrifugal Pump		Centrifugal Pump
Flow(m ³ /H)	18/15/15	30/28/28	45/40/40
Suction Port Diameter(mm/inch)	40	50	80
Discharge Port Diameter(mm/inch)	40/25/25	50/40/40	65/40/40
Total Head Lift(m)	80/80/80	55/55/55	75/75/75
Suction Head Lift(m)	7	7	7
	Engine		
Model	GB200	GB200	188F
Engine Type	4-stroke Gasoline Engine		
Displacement (cc)	196	196	389
Max Power Output(W)	4500	4500	7900
Starting System	Recoil		
Engine Oil Capacity (ml)	600	600	1100
Recommended Oil	SAE 10W-30		
Fuel Tank Size (L)	2.6	2.6	5.2
	Packing Details		
Outside Packing Dimensions (mm) (L x W x H)	545×440×475	545×440×475	620×535×545
Net Wieght (kg)	33	27	50
Certification	CE/EC/EPA	CE/EC/EPA	CE/EC





GASOLINE CHEMICAL PUMPS



MG20

1. Designed for pumping industrial and agricultural chemicals.
2. The MG20 features EPDM seals, a type of rubber material that is designed to be compatible with a wide range of chemicals.
3. The engine is easy starting and provides ample power for the toughest conditions.
4. The MG20's reinforced thermoplastic housing, volute & impeller improve chemical resistance.
5. The frame protects the pump, while offering a convenient tie down location for transport.
6. Protects the pump by shutting the engine off when low oil is detected.

Model	MG20
Pump	
Pump type	Plastic Centrifugal Pump
Flow(m ³ /H)	35
Suction Port Diameter(mm/inch)	50/2
Discharge Port Diameter(mm/inch)	50/2
Total Head Lift(m)	30
Suction Head Lift(m)	7
Engine	
Model	GB200
Engine Type	4-stroke Gasoline Engine
Displacement (cc)	196
Max Power Output(W)	4500
Starting System	Recoil
Engine Oil Capacity (ml)	600
Recommended Oil	SAE 10W-30
Fuel Tank Size (L)	2.6
Packing Details	
Outside Packing Dimensions (mm) (L x W x H)	560×440×460
Net Wieght (kg)	25
Certification	CE/EC/EPA



MINI SERIES
2000



ZSVP SERIES
2500



ZSHP SERIES
2600
3200

MINI SERIES



MINI2000

1. Lightweight Design and MINI Size: Flexible operation, easy for transportation & storage;
2. Throttle Control Mechanism + Clutch Drive Design : Safe & reliable, and more economical.
3. Ergonomic Design: Easy and convenient to use.



Model	MINI2000
Performance	
Max. Pressure(PSI)	2000
Max. Flow(GPM)	1.8
Engine	
Model	NP150
Engine Type	OHV, Air Cooling, 4 Stroke
Displacement (cc)	149
Starting System	Recoil
Engine Oil Capacity (ml)	400
Recommended Oil	10W-30
Fuel Tank Size (L)	0.75
Running time(h)	0.7
Pump	
Pump Type	Axial cam pump
Adjustable Pressure	NO
Thermal Relief Valve	YES
Chemical Injector	YES
EZ-Start Pump Valve	YES
Overall	
Frame Type:	2-Wheel Type
Wheels:	YES
Hose	
Hose Storage:	Hook
Hose Length:	7.6m(Optional)
Hose Material:	PVC
Hose Diameter:	1/4 Inch
Hose Connections:	M22x1.5
Spray Gun	
Spray Gun Connection:	M22x1.5
Spray Gun Grade:	Domestic use
Spray Gun Wand:	Chrome-plated Iron
Spray Tips:	YES
Turbo Nozzle:	NO
Accessories	
Spark Plug Socket, High Pressure Hose, Nozzle, Gun Wand, Manual	
Packing Details	
Outside Packing Dimensions (mm) (L x W x H)	455x335x575
Net Weight (kg)	16Kg
Certifications	CE/EC/EPA





ZSVP2500 / 2800

1. Lightweight rack structure: Lighter and more convenient.
2. Choosing Piston pump : Using the world famous AR piston pump, the quality is guaranteed; Configuration of easy -start valve, makes the start more comfortable; temperature control valve makes the washer safe and reliable.
3. Spray gun, High pressure pipe: Good pressure-bearing, safe and reliable.
4. Sprinkler: Configuration plug-in 0 °, 25 °, 40 °, suction nozzle, to meet the different cleaning conditions and quickly replacement.
5. Ergonomic Design: The operating parts of a reasonable location, makes it easy to use.

Model	ZSVP2500	ZSVP2800
Performance		
Max. Pressure(PSI)	2500	2800
Max. Flow(GPM)	2.4	2.6
Engine		
Model	XP160A	XP200A
Engine Type	OHV, Air Cooling, 4 Stroke	OHV, Air Cooling, 4 Stroke
Displacement (cc)	159	196.0
Starting System	Recoil	Recoil
Engine Oil Capacity (ml)	550	600
Recommended Oil	10W-30	10W-30
Fuel Tank Size (L)	1.3	1.3
Running time(h)	1.0	1.0
Pump		
Pump Type	Axial cam pump	Axial cam pump
Adjustable Pressure	NO	NO
Thermal Relief Valve	YES	YES
Chemical Injector	YES	YES
EZ-Start Pump Valve	YES	NO
Overall		
Frame Type:	2-Wheel type	2-Wheel type
Wheels:	YES	YES
Hose		
Hose Storage:	Hook	Hook
Hose Length:	7.6m(Optional)	7.6m (Optional)
Hose Material:	PVC	PVC
Hose Diameter:	1/4 Inch	1/4 Inch
Hose Connections:	M22×1.5	M22×1.5
Spray Gun		
Spray Gun Connection:	M22×1.5	M22×1.5
Spray Gun Grade:	Domestic use	Domestic use
Spray Gun Wand:	YES	YES
Spray Tips:	YES	YES
Turbo Nozzle:	NO	NO
Accessories		
Spray Gun, Gun Wand, Nozzle, Hose, Spark Plug Socket, Manual		
Packing Details		
Outside Packing Dimensions (mm) (L x W x H)	595×495×555	595×495×555
Net Weight (kg)	23	24
Certifications	CE/EC/EPA/CARB	CE/EC/EPA/CARB





ZSHP 2600/3200

- 1.Full Protection Rack Structure: Φ32mm hose diameter, wrapped frame structure makes the effective protection of the engine and pump available;
- 2.Choosing Piston Pump : Using the world famous AR piston pump, the quality is guaranteed; Configuration of easy -start valve, makes the start more comfortable; temperature control valve makes the washer safe and reliable.
- 3.Spray gun, High pressure pipe:Good pressure-bearing, safe and reliable.
- 4.Sprinkler: Configuration plug-in 0 °, 25 °, 40 °, suction nozzle, to meet the different cleaning conditions and quickly replacement.
- 5.Ergonomic Design: The operating parts of a reasonable location, makes it easy to use.

Model	ZSHP2600	ZSHP3200
Performance		
Max. Pressure(PSI)	2600	3200
Max. Flow(GPM)	2.4	2.9
Engine		
Model	GB200	GB200
Engine Type	OHV, Air Cooling, 4 Stroke	
Displacement (cc)	196	196
Starting System	Recoil	Recoil
Engine Oil Capacity (ml)	600	600
Recommended Oil	10W-30	10W-30
Fuel Tank Size (L)	2.6	2.6
Running time(h)	1.4	1.4
Pump		
Pump Type	Axial cam pump	
Adjustable Pressure	NO	NO
Thermal Relief Valve	YES	YES
Chemical Injector	YES	YES
EZ-Start Pump Valve	YES	YES
Overall		
Frame Type:	2-Wheel type	2-Wheel type
Wheels:	YES	YES
Hose		
Hose Storage:	Hook	Hook
Hose Length:	7.6m(Optional)	7.6m(Optional)
Hose Material:	PVC	PVC
Hose Diameter:	1/4 Inch	1/4 Inch
Hose Connections:	M22×1.5	M22×1.5
Spray Gun		
Spray Gun Connection:	M22×1.5	M22×1.5
Spray Gun Grade:	Domestic use	Domestic use
Spray Gun Wand:	YES	YES
Spray Tips:	YES	YES
Turbo Nozzle:	NO	NO
Accessories		
	High Pressure Hose,Spray Gun, Gun Wand, Nozzle, Manual, Spark Plug Socket	Sprary Gun, Gun Wand, Nozzle, Hose, Spark Plug Socket, Manual
Packing Details		
Outside Packing Dimensions (mm) (L x W x H)	585×505×600	585×505×600
Net Wieght (kg)	28	29
Certifications	CE/EC/EPA	CE/EC/EPA