

Model	PH6500(E)A PH8000(E)A			
Generator				
Starting System	Recoil/Electrical starting			
Alternator Material	100% CU			
Frequency (Hz)	50 Hz	60 Hz	50Hz	60Hz
Voltage(V)	230	120(120-240)	230	120(120-240)
Rated output(KW)	5	5.5	6.5	7
Max output (KW)	5.5	6	7	7.5
THD(%)	≤25			
Running time at 50% loading (H)	9.5	9	8.5	8
Fuel Tank Size(L)	23		23	
Noise dB(A)	97		97	
Insulation Grade	F		F	
Engine				
Model	FH420(E)		FH420(E)	
Engine Type	OHV.Air Cooling ,4 Stroke			
Displacement(cc)	420		420	
Packing Details				
Outside Packing Dimensions (mm) (LxWxH)	715x545x605			
Net weight(kg)	80		85	
Certification(kg)	CE/EC	EPA/CARB	CE/EC	EPA/CARB

PH 3500-8500



Model	KH3500(E)	
Generator		
Starting System	Recoil/Electrical starting	
Alternator Material	100% CU	
Frequency (Hz)	50 Hz	60Hz
Voltage (V)	230	120(120-240)
Rated output(KW)	3	3
Max output(KW)	3.3	3.3
THD(%)	≤25	
Running time at 50% loading (H)	9.5	10
Fuel Tank Size(L)	13	
Noise dB(A)	98	
Insulation Grade	F	
Engine		
Model	FH210(E)	
Engine Type	OHV.Air Cooling ,4 Stroke	
Displacement(cc)	208	
Packing Details		
Outside Packing Dimensions(mm) (LxWxH)	635x455x525	
Net weight(kg)	50	
Certification	CE/EC	EPA/CARB

KH 3500-8500



MOTOR GENERATOR