



Gol Pumps Technology Inc.

www.golpumps.us



Single Phase Solar Pumping Inverter

High-efficiency • Reliable • Safe • Low-cost

Solving your water problems
in real time with more water output

Features

- ◆ 1:1 match with single phase AC pumps with strong overload capacity;
- ◆ Solar power tracking efficiency can reach 99% with advanced MPPT algorithm;
- ◆ IP65 design, Can continuous full-load operation between -25°C to +60°C;
- ◆ Remote monitoring start and stop with RS485 & GPRS communication;
- ◆ Perfect protection system: undervoltage protection, overload protection, overvoltage protection, overcurrent protection, dry protection, short-circuit protection, etc.;
- ◆ High efficiency, low noise, fanless design, long system lifespan, safe and reliable;
- ◆ Reduce starting power and 30% more water output with advanced inverter control algorithm;
- ◆ Reduce solar panels configuration and save costs with low solar operating voltage.

Location: 3750 NW 114 AVE #6, Miami, FL 33178

Ph: +1 (786) 615 8984

Fax: +1 (786) 615 7043

www.golpumps.us

info@golpumps.com



Parameters:

LS Series				
Model	JNP750LS	JNP1K1LS	JNP1K5LS	JNP2K2LS
DC Input				
DC Max. Input Voltage	440Vdc			
Recommended MPPT Voltage	110~400V	120~400V	150~400V	150~400V
Max. MPPT Efficiency	>99%			
Number of String	2			
AC Output				
Max. Applicable Motor Output Power	750W	1100W	1500W	2200W
Rated Output Voltage	220/230/240Vac			
Output Frequency Range	0~50/60Hz			
Max. Output Current	6A	9A	11A	15A
System				
Protection Level	IP65			
Protection Class	I			
Operating Temperature	-25~60°C(above 60°C need derate operating)			
Cooling Way	Nature Cooling			
Display	LCD			
Communication	RS485/GPRS(optional)			
Altitude	3000m (above 3000m need derate operating)			
Noise Emission	<50dB			
Compliance	EN 50178; IEC/EN 62109-1 ; IEC 61800-5-1			
Dimension (L/W/H) (mm)	350/278/179			420/310/211
Weight(Kg)	9.5	9.5	9.5	14.5
Warranty	3 years			
Grid Input	Include (manual switch; external)			