



TG20/30

- 1.The engine is easy starting and provides ample power for the toughest conditions.
- 2.The TG features abrasion-resistant silicone-carbide seals for extended wear.
- 3.The frame protects the pump, while offering a convenient tie down location for transport.
- 4.The cast iron volute and impeller reduces case wear, increasing the life of the pump.
- 5.Protects the pump by shutting the engine off when low oil is detected.
- 6.The TG is designed for quick and easy service.
- 7.Providing metal filter with solid size capacity 14mm.

Model	TG20	TG30
Pump		
Pump type	Centrifugal Pump	
Flow(m ³ /H)	35	55
Suction Port Diameter(mm/inch)	50/2	80/3
Discharge Port Diameter(mm/inch)	50/2	80/3
Total Head Lift(m)	30	25
Suction Head Lift(m)	6	6
Allowed Max. Solid Size Diameter(mm)	14	22
Engine		
Model	GB200	GB200
Engine Type	4-stroke Gasoline Engine	
Displacement (cc)	196	196
Max Power Output(W)	4500	4500
Starting System	Recoil	Recoil
Engine Oil Capacity (ml)	600	600
Recommended Oil	SAE 10W- 30	
Fuel Tank Size (L)	2.6	2.6
Packing Details		
Outside Packing Dimensions (mm)	570 x 495 x 485	570x495x485
(L x W X H)		
Net Wieght (kg)	33	38
Certification	CE/EC/EPA	CE/EC/EPA