



## WG20/30

- 1.The engine is easy starting and provides ample power for the toughest conditions.
- 2.The WG Serial features Graphite ceramics seals for extended wear.
- 3.The frame protects the pump, while offering a convenient tie down location for transport.
- 4.The cast iron volute and impeller reduces case wear, increasing the life of the pump.
- 5.Protects the pump by shutting the engine off when low oil is detected.

Model	WG20	WG30
<b>Pump</b>		
Pump type	Centrifugal Pump	
Flow(m <sup>3</sup> /H)	35	55
Suction Port Diameter(mm/inch)	50/2	80/3
Discharge Port Diameter(mm/inch)	50/2	80/3
Total Head Lift(m)	30	30
Suction Head Lift(m)	7	7
<b>Engine</b>		
Model	GB200	GB200
Engine Type	4-stroke Gasoline Engine	
Displacement (cc)	196	196
Max Power Output(W)	4500	4500
Starting System	Recoil	Recoil
Engine Oil Capacity (ml)	600	600
Recommended Oil	SAE 10W- 30	
Fuel Tank Size (L )	2.6	2.6
<b>Packing Details</b>		
Outside Packing Dimensions (mm)	515 x 415 x 415	530x415x445
(L x W X H)		
Net Wieht (kg)	24	24
Certification	CE/EC/EPA	CE/EC/EPA

**GASOLINE WATER PUMPS**