

Gol Pumps Thechnology

DATA SHEET

Thin Submersible Pump GOL PUMPS 3" Inch Pump for 3.5" inch well

Gol Pumps Technology INC
3750 NW 114 Ave No: 6zip : 33178 Miami FL. USA
Tel: +1 (786) 615 - 8984 & (786)452-9775 * Fax: +1*(786) 615-7043
Email : info@golpumps.com * www.golpumps.com * www.golpumps.us

Pump Data

Brand : GOL PUMPS
Model : G3SD - M 2/28
Flow Rate: 5 GPM
Head Rate: 560 FEET
Head Max: 590 FEET
Flow Max: 13 GPM
RPM : 3450 rpm
Normal Power P2 : 2 HP
Fluid: Water
Fluid Temperature: at about 25 °C.
Density: water 1.0 kg/Dm³
Fluid Viscosity: 8.90 × 10⁻⁴ Pa-s
With Float switch: NONE
Kind of Workiny: Submersible
Delivery size: 1 1/4" NPT
Suction size: With Strainer
Made in : CHINA

Motor Data

Power P2: 1.5 KW
Power P1: *
Phase (PH): 1
Rate Voltage : 220 V
Capacitor Need : 50/450 µF / V
Ferequency : 60 Hz
Rated Speed (rpm): 3450 rpm
Current (A): 9.7 A
Cos φ : 0.95
Degree of Protection (IP): IP 68
Safety Protection Included: F
length of Cable : 2 M
Kind of Plug : NONE
Ambient Temp : 40°C = 104°F

Other Pump Data

Impeller Size (mm) : *
Pressuer Rating : PN 16
Min. Fluid Temp : 10°C = 50°F
Max. Fluid Temp : 35°C = 95°F
Ambient Temp : 40°C = 104°F
Humidity % : 100%

Special Specification

Installation status : Vertical
Variable frequency : NONE
Solid Passage 0.25%

Materials

Pump Body : AISI 304 SS
Support: AISI 304 SS
Impeller: Plastic POM
Mechanical Seal: Graphite\Ceramic
Rubber: NBR
Pump Shaft: AISI 304 SS
Strainer: AISI 304 SS
outer cover: Cast Iron
Motor Case: AISI 304 SS

Shaft Seal



Type: *
Stationary Part: Ceramic
Rotating Part: Graphite
Elastomer: NBR

Pump and Motor specification optional

With Booster System: None
With Complack: None
Special Material: None
Specail Voltage: None

Protection system required

External Flout switch: NONE
Minimum Starter: Over Load and Capacitor Box Include



Weight : 15 Kg

Standard Approve



Applicant:

For Water Supply from
Wells or Reservoirs for
Domestic Use for Civil and
Industrial Applications for
Garden Use and Irrigation

Dimention in

	in	mm
P		779
M		543
T		1322
DN		1 1/4"
D1		75
D2		73