


### Pump Data

Brand :	Gol Pump		
Model :	GKT- 732		
Head Rate:	53 FEET	Flow Rate:	213 GPM
Head Max:	73 FEET	Flow Max:	453 GPM
Head Min:	20 FEET	Flow Min:	5 GPM
RPM :	3600		
Normal Power P1 :	7.5 HP		
Fluid:	Water		
Fluid Temperture:	at about 25 °C.		
Density:	water 997 kg/m <sup>3</sup>		
Fluid Viscosity:	8.90 × 10 <sup>-4</sup> Pa-s		
With Float switch	NONE		
Self Priming	Submersible		
Delivery size	4" NPT		
Suction size	With Strainer		
Made in :	TAIWAN		

**GKT - 732**



### Motor Data

Power P2:			
Power P1:	5.625 KW		
Phase (PH):	3		
Rate Voltage :	440 V		
Capacitor Need :	*	µF	
Ferequency :	60 Hz		
Rated Speed (rpm):	3600 rpm		
Current (A):	8.5 A		
Cos φ :	0.85		
Degree of Protection (IP):	IP68		
Safety Protection Included :	*		
length of Cable :	5.5 10	mm2×	mm
Kind of Plug :	*		
Ambient Temp :	40°C = 104°F		

### Other Pump Data


Impeller Size (mm) :	*		
Pressuer Rating :	PN 16		
Min. Fluid Temp :	10°C = 50°F		
Max. Fluid Temp :	25°C = 77°F		
Ambient Temp :	40°C = 104°F		
Humidity % :	100%		

### Special Specification

Installation status :	Ver & Hor
Variable frequency :	NONE
Solid Passage	50 × 11 mm

### Materials

Pump Body :	Cost Iron
Support:	Cast Iron
Impeller	High Chromium
Mechanical Seal:	Silicon Carbide
Rubber	NBR
Pump Shaft:	Stainless steel
Strainer	Stainless steel
outer cover:	Stainless steel
Motor:	Stainless steel



### Shaft Seal

Type:	*
Stationary Part	Silicon Carbide
Rotating Part	Carbon
Elastomer	NBR

Weight :77 Kg

Standard Approve

CSA



UL



CE



Applicant:

Basement Drainage Water Supply for Landscape and Water Feature  
 Agricultural and Horticultural Irrigation Water Supply for Fountains and  
 Water Features Water Discharge Work for Ships Any Kind of Standing  
 Water and Water Discharge Waste Water Treatment Construction  
 Engineering Drainage System Agricultural Irrigation Fishing and Spraying

Dimention

in mm

A	272
B	125
C	720

### Pump and Motor specification optional

With Booster System	None
With Complack	None
Special Material	None
Specail Voltage	None

### Protection system required

External Flout switch	None
Minimum Starter	Starter SWT