


Pump Data

Brand :	Gol Pump		
Model :	GPDC48V/I -50-3- 0.4-1		
Head Rate :	116 FEET	Flow Rate:	6.6 GPM
Head Min:	30 FEET	Flow Max:	12.2 GPM
Head Max:	150 FEET	Flow Min :	2.2 GPM
RPM :	5000 rpm		
Normal Power P1 :	0.53 HP		
Fluid:	Water		
Fluid Temperature:	at about 25 °C		
Density:	water 997 kg/m ³		
Fluid Viscosity:	8.90 × 10 ⁻⁴ Pa·s		
With Float switch	NONE		
Kind of Pump	Submersible		
Delivery size	1" Outlet with hose head		
Suction size	With Strainer		
Made in :	CHINA		



Motor Data

KIND OF Motor	with Brush		
Power P1:	0.4 KW		
Phase (PH):	DC SINGLE PHASE		
Rate Voltage :	48 VDC		
Capacitor Need :	NONE		
Ferequency :	DC		
Rated Speed (rpm):	5000 rpm		
Current (A):	8 A		
Cos φ :	1		
Degree of Protection (IP):	IP 68		
Safety Protection Included :	E		
length of Cable :	20 M		
Kind of Plug :	NONE		
Ambient Temp :	40°C = 104°F		

Other Pump Data

Impeller Model :	Noryl		
Pressuer Rating :	PN 16		
Min. Fluid Temp :	0°C = 32° F		
Max. Fluid Temp :	90°C = 234°F		
Ambient Temp :	40°C = 104°F		
Humidity % :	100%		

Special Specification

Installation status :	Vertical		
Variable frequency :	NONE		
Solid Passage:	80	Gr/M3	

Materials

Pump Body :	Cast Iron
Diffuser :	Noryl
Impeller:	Noryl
Mechanical Seal:	CE/CA/NBR/INOX
Rubber:	NBR
Pump Shaft:	SUS 304
Strainer:	SUS 304
outer cover:	Cast Iron
Motor:	Cast Iron

Shaft Seal

Type:	*
Stationary Part:	Ceramic
Rotating Part:	Carbon
Elastomer:	NBR

Standard Approve :

Weight : * Kg


CE



Rev : 2021 / 02



Direct Connection to Solar Panel



Applicant :

- Irrigation, Livestock, Garden Fountains,
- Home Supply, Large Scale Watering System
- Commercial Establishments, Solar Water Treatment
- DC Solar Water Pump Connect to Solar Panel Directly
- DC Solar Water Pump Connect to Battery Directly